


Technical Datasheet		Conveyor Belt		
Belt type 2 LRWAF 905 SQPR FR3 35°		Belt No.2140		
<i>Applications</i>				
<ul style="list-style-type: none"> ▪ Internal transport, post offices and distribution centers ▪ General purpose conveying ▪ Luggage handling in airports and passenger terminals 				
<i>Construction</i>				
	Top side	Bottom side		
	PVC 35 Shore A 0.50mm SQPR Square Black	Polyester Rigid Whisper Antistatic fabric		
	Tension member	Splice		
	Polyester Fabric 2ply	Finger		
<i>Dimensions</i>		<i>Properties</i>		
Width/Roll(max.)	3,000 mm			
Length (max.)	100m			
Total thickness	2.4 mm			
Weight	2.5 kg/m ²			
Please contact Nitta if you need other dimensions.				
<i>Regulatory compliance</i>				
Flame Retardant (ISO 340)				
<i>Features</i>				
Antistatic Flame Retardant				
<i>Properties</i>				
Minimum pulley diameter Flexing	40 mm			
	Back flexing			
Standard elongation Tension after relaxation at 0.5%	60 mm			
	0.5 %			
Initial tension at 1.0% Tension after relaxation at 1.0%	2.0 N/mm			
	8.0 N/mm			
Operating temperature range	4.0 N/mm			
	-5~70 °C			
NITTA CORPORATION				